

WATERPROOFING



SEALERS



HARDENERS

ADHESIVES



EPOXIES



GROUTS

CONCRETE REPAIR



OVERLAYS

POLYURETHANES

CONSTRUCTION CHEMICALS

www.tex-crete.com

EPOXIES



EpoCrete 100

Clear Epoxy Floor Coating

A two-component, high solid-content, clear epoxy resin floor coating that cures to a glossy finish with high chemical resistance.

EpoCrete 100W

Water Based Clear Epoxy Coating

An environmentally friendly, low VOC, two-component, high solid content, clear epoxy floor coating that cures to a high gloss finish.



EpoCrete 150

Solvent Based Epoxy Floor Coating

An economical two-component, solvent-based, colored, 150 micron DFT matte epoxy floor coating for moderate abrasion resistance applications.

EpoCrete 180

Non-Toxic Epoxy Protective Coating

A two-component, solvent-free, non-toxic, colored epoxy floor coating with excellent chemical and abrasion resistance.



EpoCrete 200

High Solid Content Epoxy Floor Coating

A high solid content, two-component, colored, 200 micron DFT, semi glossy epoxy floor coating for moderate to high abrasion resistance applications. Use with quartz granulars for anti-skid finish.

EpoCrete 250

Solvent-Free Epoxy Floor Coating

A high performance, solvent free, two-component, 250 micron DFT, glossy epoxy floor coating for high abrasion resistance applications. Use with quartz granulars for anti-skid finish.



EpoCrete 250W

Water Based Epoxy Floor Coating

A low VOC, environmentally friendly, high performance, colored, two-component, 250 micron DFT, glossy epoxy floor coating. Use with quartz granulars for anti-skid finish.

EpoCrete 400

High Build Epoxy Floor Coating

An ultra high performance, two-component, high build, solvent-free epoxy floor coating applied in 400 micron DFT for extreme abrasion and impact resistance and compressive strength exceeding 150 MPa.

PRIMERS

EpoPrime EP / EP1

Epoxy Floor Primer

A solvent-based, clear, low viscosity epoxy floor primer applied to masonry surfaces to receive a resinous coating. 50% solid content for EP1 grade, 75% solid content for EP grade.

EpoPrime 100TG

High Build Epoxy Floor Primer

A high performance, clear, solvent-free, low viscosity high film thickness epoxy floor primer. Suitable for receiving silica aggregates before application of top coats.



POLYURETHANES

ElastoCrete 202

Two Component PU Waterproofing & Primer Coat

A high solid content, high build (200 micron DFT), two component, flexible, aromatic polyurethane coating for waterproofing & priming concrete surfaces. May also be used as a protective coating on light-duty applications.

ElastoCrete 210

Water Based Polyurethane Waterproofing Coat

A single component, water-based, aliphatic, ultra high flexibility (260%) polyurethane top coat for waterproofing and protecting concrete surfaces.

ElastoCrete 212

Water Based Clear Polyurethane Coat

A two component, water-based, aliphatic, clear polyurethane sealer for waterproofing and protecting concrete surface. Available matte or glossy.

ElastoCrete 222

Water Based Polyurethane Top Coat

A two component, high build (200 micron), water-based, colored, aliphatic, matte or glossy polyurethane top coat with high chemical and abrasion resistance.

ElastoCrete 4000

Polyurethane Top Coat

An economical, solvent-based, aliphatic, colored or clear flexible polyurethane top coat for high-build traffic deck coating systems.

ElastoCrete 5000

Heavy Duty Polyurethane Floor Coating

A high performance, solvent-free, two component, aromatic, flexible polyurethane intermediate wearing coat for heavy duty applications.

ElastoCrete 6500

Heavy Duty Polyurethane Top Coat

A high performance, two-component, high solid content, UV-resistant, flexible, highly abrasion resistance polyurethane traffic floor top coat.



CEMENTITIOUS OVERLAYS



PaveCrete 220

Micro Topping Skim Coat

A high performance, single component, polymer-fortified, colored, cementitious micro topping applicable by trowel, spray gun, brush, sponge or roller in thicknesses from featheredge to 1 mm for restoration and renovation.

LevelCrete 900

Self-Leveling Underlay

A single component, uncolored, flowable, self-leveling cementitious overlay that cures quickly to a hard-wearing surface. Applied in up to 30 mm for leveling existing floors or correcting construction errors.



TopCrete 600

Screed Overlay

A single component, polymer-modified, colored cementitious topping applied by trowel for resurfacing floors in 10 to 30 mm thicknesses.

RESINOUS OVERLAYS



EpoCrete 1000

Quartz Carpet Overlay

A trowel-applied, three-component system composed of colored quartz aggregates and solvent-free clear epoxy. Applied in 1-5 mm thicknesses for a decorative appearance while providing a hygienic, anti-skid surface.

EpoCrete 2000

Self-Leveling Epoxy Overlay

A high performance, three-component, high solid-content, flowable epoxy coating applied in thicknesses up to 3 mm where extreme abrasion resistance is required such as production facilities and aircraft hangers.

EpoCrete 2000W

Water Based Self-Leveling Epoxy Overlay

An environmentally friendly, low VOC, three component, high performance, flowable epoxy coating applied in thicknesses up to 3 mm where extreme abrasion resistance is required.



EpoCrete 2000P

Pearl Epoxy Coating

A flowable, self-leveling epoxy formulated with unique additives and special pigments applied in thicknesses of 1-2 mm to produce a glittering decorative surface.

EpoCrete 5000

High-Performance Epoxy Floor Screed

A trowel-applied, ultra high performance, three-component, high build epoxy floor screed applicable in 1-5 mm thickness.

HARDENERS

PaveCrete 100

Basalt-Based Floor Hardener

A ready-to-use, basalt aggregate based, colored or uncolored, metal-free, cement-based floor hardener for application by dry-shake method over freshly poured concrete. Suitable for use in areas where very high abrasion is required, such as warehouses, manufacturing plants, garages, and aircraft hangers. Increases abrasion resistance by 400%.



PaveCrete 101

Silica-Based Floor Hardener

A ready-to-use, silica aggregate based, colored or uncolored, metal-free, cement-based floor hardener for application by dry-shake method over freshly-poured concrete to increase abrasion resistance by a minimum of 300%. Suitable for high abrasion resistance areas such as garages and power stations.



PaveCrete 103

Emery-Based Floor Hardener

A ready-to-use, emery aggregate based, colored or uncolored, metal-free, cement-based floor hardener for application by dry-shake method over freshly-poured concrete. Suitable for use in areas where maximum abrasion resistance is required, such as aircraft hangers, metal workshops, and garages. Increases abrasion resistance by 300-550%.



PaveCrete 200

Premium Color Hardener

A ready-to-use, colored, metal-free, cement-based floor hardener based on finely graded silica aggregates for application by dry-shake method over freshly-poured concrete. Formulated with specially-selected graded silica aggregates and additives for decorative concrete applications.



A-Z 103

Surface Hardener & Sealer

A ready-to-use liquid floor hardener and dust proofer based on water-soluble sodium silicate synthetic resins. Applied by roller or sprayer on old and newly cured concrete surfaces and other porous surfaces. For external or internal applications.

SoilCrete PA

Acrylic Copolymer Soil Stabilizer

A ready-to-use, water-soluble, synthetic polyvinyl acetate acrylic copolymer emulsion. Dilute on site to be mixed in with the soil or applied topically to the surface to stabilize the soil, reduce erosion, and control dust.

EPOXY



FlexCrete 200

Coal Tar Epoxy Waterproofing Coating

A two-component, solvent based, flexible, epoxy-modified coal tar coating with high chemical resistance for protecting and waterproofing sewage tanks, foundations, drainage pipes, traffic decking, and metal surfaces in aggressive environments.



FlexCrete 400

Elastomeric Epoxy Coating for Water Tanks

A two-component, non-toxic, flexible, epoxy polysulfide elastomeric coating that provides high elongation (40%) and high build at 400 microns per coat for protecting and waterproofing potable water tanks.

FlexCrete 500

Elastomeric Epoxy Coating For Sewage Tanks

A two-component, epoxy polysulfide flexible coating with 35% elongation, high build at 500 microns per coat, and high chemical resistance for waterproofing and protecting sewage tanks, pile heads and swimming pools.



EpoCrete 180

Non-Toxic Epoxy Protective Coating

A two-component, solvent-free, non-toxic, colored epoxy coating with excellent chemical and abrasion resistance for protecting and waterproofing horizontal and vertical concrete and metal surfaces where contact with food stuffs and drinking water may occur.



POLYURETHANE

ElastoCrete 201

Single Component PU Waterproofing Coating

A liquid-applied, single component, elastomeric polyurethane coating that provides high elongation of 115% and high film thickness of 200-230 micron DFT per coat for protecting and waterproofing concrete and other masonry surfaces subjected to prolonged water exposure and moisture such as kitchens, bathrooms, retaining walls, planter boxes and other wet areas.

ElastoCrete 202

Two Component PU Waterproofing & Deck Coating

A high solid content, two component, liquid applied, flexible, aromatic polyurethane coating for waterproofing concrete surfaces on internal applications where abrasion resistance may also be required such as chemical plants, parking decks, balconies, passageways, and roots.

CEMENTITIOUS

ProofCrete 709

Two-Component Cementitious Waterproofing Coating

A cement-based, cold-applied, permanently flexible membrane with over 35% elongation and good adhesion to concrete for waterproofing concrete masonry and building exteriors, walls, water tanks, roofs and wet area floors such as kitchens, balconies and bathrooms.

ProofCrete 710

Single-Component Cementitious Waterproofing Coating

A cement-based, cold-applied, permanently flexible membrane composed of a factory blend of cement, fillers, and acrylics for waterproofing concrete masonry and building exteriors, walls, water tanks, roofs and wet area floors such as kitchens and balconies.

ProofCrete 711

Waterproofing Coating By Crystallization

A cement-based, cold-applied membrane that densifies and blocks the porous concrete surface by crystallization for waterproofing concrete masonry and building exteriors, walls, water tanks, roofs and wet area floors such as kitchens and balconies.



ACRYLIC

ProofCrete 700

Acrylic Waterproofing Membrane

A liquid-applied, permanently flexible, economical acrylic waterproofing elastomer coating suitable for waterproofing wet areas such as kitchens, bathrooms, building exteriors and roofs.

ProofCrete 704

High Content Acrylic Waterproofing Membrane

A high performance, liquid-applied, permanently flexible, high acrylic content waterproofing elastomer with over 300% elongation for waterproofing wet areas such as kitchens, bathrooms, and building exteriors and roofs.



BITUMINOUS

ProofCrete RB

Rubberized Bitumen Emulsion Coating

A cold-applied, highly rubberized, polymer-modified, blend of selected bitumens emulsified in water suitable as a damp-proofing membrane, protective coating and vapor seal for concrete, masonry, mastic asphalt, and roofing felt.



CEMENTITIOUS



PatchCrete 100

Special Repair Mortar

A single component, polymer-modified, shrinkage resistant, cement based leveling and fair-facing concrete restoration coating applicable in thicknesses ranging from featheredge to 3 mm over large areas to produce a smooth surface.



PatchCrete 101

Multi-Use Repair Mortar

A single component, cement-based, polymer-modified, fiber reinforced concrete patching and repair compound. Available in fine, medium and coarse grades and applicable in thicknesses from featheredge to 10 cm for vertical, horizontal, and overhead patching and general concrete repairs.

PatchCrete 102

Crack Filler

A high performance, single component, polymer modified, very fine grain grout for repairing and fair-facing concrete fine cracks up to 4 mm wide.



PatchCrete 601

Non-Shrink Structural Grout

A high-performance, polymer modified, non-shrink grout designed for maximum flowability and strength for grouting machine bases and column base plates, and filling tie rod holes, anchor bolts, dowels and crane rails.



EPOXY

MortCrete 3000

Multi-Purpose Epoxy Mortar

A two-component, solvent-free concrete patching and repair epoxy mortar suitable for concrete repair and patching where high compressive strength and chemical resistance are required, such as car park decks and heavy-industrial warehouses before application of a resinous protective coating system.

TOPICAL SEALERS

A-Z Mega Sealer

Water-Based Acrylic-Urethane Sealer

A single component, UV resistant, matte finish acrylic-urethane sealer for protecting masonry surfaces against stains and moisture penetration.

A-Z Super Sealer

Solvent-Borne Acrylic Sealer

A deep-penetrating, oil and moisture repellent, gloss or matt finish Ethyl Methacrylate coating for protecting concrete and absorbative surfaces.

A-Z Ultra Sealer

Solvent-Borne Acrylic Sealer

A deep-penetrating, low viscosity, oil and moisture repellent, gloss or matt finish styrene acrylic resin coating for protecting concrete and absorbative surfaces against stains and discoloration.

ElastoCrete 212

Water Based Clear Polyurethane Sealer

A two component, water-based, aliphatic, clear polyurethane sealer for waterproofing and protecting concrete surface. Available matte or glossy.



PENETRATING SEALERS

A-Z Penetrating Sealer LS

Masonry Water Repellent

An aqueous solution of potassium methyl silicate that impregnates porous surfaces to impart water-repellency to concrete, plaster, and natural stone.

A-Z Penetrating Sealer SB

Masonry Water Repellent

A deep penetrating silicone sealer based on silane/siloxane diluted in organic solvents that imparts water-repellency to a variety of porous materials.

A-Z Penetrating Sealer SMK

Masonry Water Repellent

A water-soluble microemulsion concentrate based on silanes and siloxanes for imparting water repellency to porous alkaline and mineral surfaces.

A-Z Penetrating Sealer WB

Masonry Water Repellent

A water-based, solventless, silane/siloxane emulsion, deep-penetrating water repellent for sealing porous alkaline and mineral surfaces against water penetration.

A-Z Penetrating Sealer OW

Penetrating Stain Repellent

A water-based mixture of silane, siloxane, and synthetic resins that penetrates porous surfaces to impart hydrophobic and oleophobic properties for stain resistance against water and oil based fluids.



TILING



FixGrout

Thin Set Tile Adhesive

A general purpose, polymer-fortified thin-set tile adhesive.

ZeitaFix

Industrial Thin Set Tile Adhesive

A high performance, polymer modified, fiber-reinforced, thin-set tile adhesive for commercial applications.

MegaFix

Flexible Pool Adhesive

A high performance, flexible, polymer-modified, thin or thick-bed, water-resistant tile adhesive for adhering tile to areas subject to permanent wet conditions such as pools and bathrooms.



ArtGrout 300

Non-Sanded Colored Tile Grout

A polymer-modified, non-shrink, smooth finish, colored tile grout for filling joints 1-6 mm wide.

ArtGrout 301

Sanded Colored Tile Grout

A polymer-modified, non-shrink, textured finish, colored tile grout for filling joints 3-12 mm wide.

ArtGrout 302

Marble and Granite Grout

A polymer-modified, non-shrink, colored grout for filling marble and granite tile joints 1-3 mm wide.

ArtGrout 303

Flexible Pool Tile Grout

A highly polymer-modified, non-shrink, non-sanded, colored grout for filling joints 1-6 mm wide subject to permanent water exposure.

ArtGrout 304

Wide Joint Tile Grout

A polymer-modified, non-shrink, colored grout for filling joints up to 20 mm wide.

ArtGrout 306

Masonry Mortar

A polymer-modified, non-shrink, colored grout for block and brick laying in joints 3-15 mm wide.



MortCrete AB10

Hygienic Epoxy Tile Grout

A three-component, solven-free, epoxy grout for gouting and adhering tiles in heavy-duty and hygienic areas.

GENERAL ADHESIVES

BondCrete

Bonding Slurry

A premium, single component, polymer-modified, cement-based bonding slurry for adhering new concrete screeds and overlays to existing concrete slabs.

BondCrete EP

Epoxy Bonding Slurry

A two-component, epoxy resin bonding slurry for bonding new concrete to existing concrete slabs.

FoamFix ST / XT

Adhesive & Base Coat

A polymer-modified, fiber-reinforced, cement-based adhesive and base coat for vertical applications. XT grade was specifically formulated for Exterior Insulation and Finish Systems (EIFS) for adhering polystyrene board to block work or plaster and for embedding reinforcing mesh onto insulation foam boards. ST grade is recommended as a base coat with fiberglass mesh on masonry surfaces and plaster boards to receive a stucco coat.

A-Z Strong Bond

Polyvinyl Acetate Latex Emulsion

A concentrated latex PVAC emulsion for bonding cementitious materials to masonry surfaces.

A-Z Super Bond

Modified Styrene Acrylic Copolymer

A ready-to-use, Styrene Acrylic copolymer for bonding cementitious materials to masonry surfaces.

A-Z Mega Bond

Acrylic Latex Emulsion

A non re-emulsifiable acrylic latex emulsion used as a bonding agent for concrete repair and topping, and a strength-enhancing admixture for surface repair.

A-Z Hi Bond

SBR Copolymer

A milky-white latex based on modified styrene butadiene copolymer emulsion used as a bonding agent for concrete repair and topping, and a bond-enhancing admixture for cementitious mixes.



P.O Box 91324
City of Industry, California 91715-1324 USA
Tel (909) 266-0709, Fax (909) 266-0711

P.O. Box 925794, Amman , 11190, Jordan
Tel (962-6) 487-4078, Fax (962-6) 488-9133

P.O. Box 31017, Sharjah, UAE
Tel (971-6) 532-1119, Fax (9716) 532-8833

الأنظمة الخرسانية المبتكرة ذ م م.

CREATIVE CONCRETE CONCEPTS LLC.

CONSTRUCTION CHEMICALS

www.tex-crete.com ● info@tex-crete.com